

### Features

- 4 x NO relay output 10A resistive or 6A fluorescent (IEC62386-208)
- Rated inrush of 492A at 1.5ms or 165A at 20ms
- Suitable for distribution board mounting on standard DIN rail
- Protected against DALI over voltage
- LED indicators for system status



### DALI device

Fully DALI compliant and compatible



### Over-voltage

Protected against DALI over-voltage conditions




### Relays

Integrates 4 normally open 10A relays



### Interface

Supports DALI-2 and IEC62386-104 over Thread




## Product range

Order code	Description
zc-relay-4	4 Channel DALI relay controller

### Features

- 4 x NO relay output 10A resistive or 6A fluorescent (IEC62386-208)
- Rated inrush of 492A at 1.5ms or 165A at 20ms
- Suitable for distribution board mounting on standard DIN rail
- Reinforced insulation between DALI and mains supply
- Protected against DALI over voltage
- LED indicators for system status

## Dimensions (mm)



## Specifications

<b>Supply voltage</b>	220 - 240 V ~ 50 Hz
<b>Control system</b>	Wired DALI-2    Wireless IEC62386-104 over Thread
<b>DALI line current</b>	2 mA
<b>Wiring</b>	1 - 4 mm <sup>2</sup> Strip 6 - 7 mm
<b>Operating temperature</b>	0 to 55°C
<b>Material</b>	PC
<b>Classification</b>	Class II
<b>Mounting</b>	DIN rail (35 mm)
<b>Ingress protection</b>	IP20
<b>Compliance standards</b>	IEC 61347-2-11 IEC 60950-1 CISPR 15 CISPR 22 EN 55015 EN 55022 IEC62386-205 IEC62386-208 IEC62386-301/302/303 EMC-2004/108/EC LVD-2006/95/EC

## Wiring diagram

